

# ODV-2D

THERMAL PRINTER VERIFIER

COMPLIANT VERIFICATION

DATA VALIDATION

EASY COMMUNICATION

DEPENDABLE DESIGN







# Eliminate expensive compliance fees by producing 100% accurate barcodes, 100% of the time.

The ODV-2D is the industry's first affordable, fully integrated solution with the ability to print, verify and validate 1D and 2D barcodes. Built on the robust T8000 printer platform, ODV-2D includes a built-in verifier that grades barcodes to ISO 15415, 15416 and 15426 standards and stores a detailed report of each transaction. Our exclusive technology reads each barcode, overstrikes the entire label of a rejected barcode, and reprints a new label. The ODV-2D delivers accelerated ROI by eliminating charge backs and fines for non-conforming labels. Advanced features allow it to integrate easily and quickly into existing applications.



#### COMPLIANT VALIDATION & PRODUCTIVITY

- Verifies full suite of 1D & 2D barcodes with up to 50 barcodes per label
- Prints up to 8ips with full barcode verification, grading and compliance verification reporting as well as barcode data validation
- Grades to ISO standards including Quiet Zone & Check Sum errors
- Full label back-up and overstrike
- Barcode "GPS" dynamically locates barcode, orientation & improved throughput
- Most affordable, fully integrated solution on the market



#### EASY COMMUNICATION & NETWORKING

- Most extensive suite of printer emulations in the industry
- PrintNet Enterprise Auto ID provides global or enterprise wide network access, control, update and reporting
- Supports Ethernet or WiFi & includes 802.11ac for faster communication & improved range
- Extensive and scalable security solutions



#### **DEPENDABLE DESIGN**

- Rugged metal enclosure with dampened hinges
- Built on the proven design of our most robust printer, the T8000
- Dual motor design for outstanding print quality & productivity
- Large 3.4" color display panel with intuitive menu and navigation keys
- Intelligent heat management for longer printhead life outstanding print quality even at top speeds

#### TIRED OF REJECTED SHIPMENTS AND COMPLIANCE FEES?

With a global increase in regulatory compliance standards and fines, it is more important than ever to ensure your products are labeled correctly with accurate barcodes. ODV-2D addresses these requirements with the ability to validate up to 50 barcodes per label INCLUDING 2D Barcodes.

The ODV-2D reads and grades every label based on ISO standards. When ODV-2D rejects a barcode, it strikes out the entire label and reprints it without operator intervention. At the end of the day you can generate a report directly from the printer with data on every label printed and graded. Archive that data and you'll never pay compliance fees again!





### WE BUILT A COMPLETE SOLUTION SO YOU DON'T HAVE TO

With the introduction of the ODV-2D we've eliminated the need for companies to piece together their own solutions from separate printers and validators. ODV-2D offers the industry's first affordable, fully integrated solution with the ability to print, verify and validate **1D and 2D barcodes.** The ODV-2D is built on the proven design of our most robust printer, the T8000.

#### MANAGE YOUR ENTIRE ENTERPRISE FROM A SINGLE LOCATION

Printronix Auto ID Data Manager (part of the PrintNet Enerprise Suite) gives you the ability to dynamically record, archive and generate reports of scanned barcode data for each printer. With the addition of our robust printer management tool, you can pull reports for your entire enterprise as well as monitor and configure printers from anywhere in the world. You can also designate events and be alerted to printer issues via email, pager or mobile phone alerts. PrintNet Enterprise is available at no charge with the purchase of an ODV-2D printer.

#### **COMBINING VERIFICATION WITH VALIDATION**

The ODV-2D is the only product available that can validate and verify barcodes as they are printed. The data printed on the label is validated to match the data sent from the host. The barcode image is verified to comply with the ISO 15415, 15416 and 15426 standards.



printronixautoid.com

## ODV-2D SPECIFICATIONS

\* Available in 203 DPI and 300 DPI

\* Dual motor ribbon drive system

\* ENERGY STAR Certified

(Independent of dpi)

Transfer and Direct

203 DPI or 300 DPI

512 MB RAM / 128 MB Flash

4.1" (104 mm)

1" (25.4 mm) 4.5" (114.3 mm)

Up to 99"

8.0" (209 mm)

1" (25.4 mm)

625 m

4.5" (114.3 mm)

Wax, Wax/Resin, Resin

Peel-Off, Rewind, Cutter

11.7" (297.2 mm) 13" (330.2 mm)

22.1" (561mm)

37 lbs. (16.7 Kg.) 46 lbs. (20.8 Kg.)

PJL, XML, and PTX-SETUP

\* 512MB RAM / 128MB Flash Memory

\* 4-32 GB SD memory card capability

Picket Fence @ 8ips / Ladder / 2D @ 6ips

Roll or Fan-Fold Labels, Tags, Paper, Film, Tickets

0.25" / 1.0" (Continuous/Tear-Off) / 0.5" (Peel-Off)

0.0025" (0.0635 mm) to 0.010" (0254 mm)

Gap, Mark, Advanced Gap, Advanced Notch

1.5" (37.5 mm) to 3.0" (76 mm)

Continuous, Tear-Off Strip, Tear-Off

#### **PRODUCT BENEFITS**

- \* High performance ARM Cortex-A9
- \* Die-cast aluminum frame w/metal door
- \* Transfer and direct printing
- \* 4" model configuration
- \* Asian Fonts (Andale and Premium)

#### \* State-of-the-art WiFi connectivity

#### PRINTER SPECIFICATIONS

Max Print Speed Print Method

Resolution Max. Print Width Printer Memory

#### **MEDIA SPECIFICATIONS**

Media Type Min. Media Width Max. Media Width Min. Media Length Max. Media Length Media Thickness Media Roll Core Diameter Max. Media Roll Diameter Media Sensing

#### **RIBBON SPECIFICATIONS**

Ribbon Type Min. Ribbon Width Max. Ribbon Width Max. Ribbon Length

#### MEDIA HANDLING MODES

Standard Options

#### PHYSICAL CHARACTERISTICS

Width Height Depth Printer Weight **Shipping Weight** 

PRINTER LANGUAGE

**IGP** Languages Line Printer Plus Languages

Job Control Languages **Optional Languages** 

#### IPDS TN5250/TN3270 PDF Level 1.7, Postscript Level 3

#### COMMUNICATION AND CONNECTIVITY / INTERFACE

Standard Interface I/O Optional Interface I/O

WiFi Security Protocol (two can be installed)

Serial RS232, USB, and Ethernet 10/100Base T Parallel, WiFi (802.11 b/g/n 2.4 GHz) (802.11 a/n/ac 5 GHz), GPIO WEP 40/128bit, WPA Personal (TKIP), WPA2 Personal (AES/CCMP), EAP-PEAP, EAP-TTLS, PEAPv0/EAP-MSCHAPv2, EAP-TLS Security Certificates

CE

PGL/VGL/ZGL/TGL/IGL/STGL/DGL/IEGL/MGL

P-Series + XQ, Proprinter, Serial Matrix, Epson









Contact your local Printronix Auto ID authorized reseller or EMEA\_Sales@PrintronixAutoID.com





Barcode Type	1D & 2D
Read Technology	5MP Camera
Barcode GPS	Yes
Max Barcodes per label	50
Overstrike Area	Full label
Validate Min. X-Dimensions	10 mils
Validate Max. X-Dimensions	60 mils
Barcode Orientation	0°, 90°, 180°, 270°
Barcode Grading	A, B, C, D, F
Grading Report	Yes
Validation Standard	Based on ISO 15415, 15416 and 15426 standards
Data Capture	AutoID Data Manager PXML Messaging Schema for 3rd Party Applications
OPERATING ENVIRONMENT	
Operating Temperature	Direct Thermal w/o accessories:
	23degF to 104degF (-5degC to 40degC)
	Thermal Transfer: 40°F to 104°F (5°C to 40°C)
Operating Humidity	20-85% Non-Condensing
Storage Temperature	23° to 140°F (-5° to 60°C)
Storage Humidity	5 to 85% Non-Condensing
POWER REQUIREMENT	Auto Range 90 - 264 VAC (48 - 62 Hz)
REGULATORY COMPLIANCES	Auto hange 50 - 204 VAC (40 - 02 112)
Emissions	FCC, CE, CCC
Safety	cTUVus, CE
Environmental	RoHS, WEEE, Energy Star
BARCODES SUPPORTED FOR VERIF	
1D Barcodes	Code 39, Code 93, Interleaved 2/5, Code 128, EAN 8 & 1
	UPC-A, UPC-E, EAN UPC add-ons, Codabar
2D Barcodes	PDF417, PDF417 Truncated, PDF417 Micro, DataMatrix,
	Datamatrix (ECC200), QR, Deleta Aztec
FONT, GRAPHIC SUPPORT	
Graphic Formats	PCX, TIFF, BMP, PNG
Font Technologies	Intellifont, TrueType, Unicode
Standard Fonts	OCRA, OCRB, Courier, Letter Gothic, CG Times,
Asian Fanta (Ontin 1 CD and)	CG Triumvirate/Bold/Condensed
Asian Fonts (Optional SD card)	Simplified Chinese, Japanese, and Korean
Andale Fonts (Optional SD card)	Simplified Chinese, Traditional Chinese, Korean, Japanese
PDF/ PostScript Level 3	35 Fonts
REMOTE MANAGEMENT SOFTWAR PrintNet Enterprise Suite	E Enterprise Grade Remote Management Solution
OPTIONS AND ACCESSORIES	Enterprise Grade Remote Management Solution
	× 2 · · ·
* WiFi 802.11 a/b/g/n/ac	* Rewind
(US/EU/CAN/China)	* Cutter
* Parallel Port Card	* Protective Cover
* GPIO	* Peel & Present
* TN5250 * DDF (Da at Carriet	* Premium Asian Font Cards
* PDF/PostScript	* Premium Andale Font Cards
* IPDS	* Andale Asian Font Cards

\* QCMC (SD Quick Change Memory Card)



### printronixautoid.com

© 2019 Printronix Auto ID Technology Inc. All rights reserved.

