

SOLID 85E

MICROPLEX®
Excellence in Print Technology

Applikations


- ... demandig media like plastic, PVC etc.
- ... label batch printing
- ... ticket printing
- ... business papers

High performances and low printing costs

Economic continuous laser printer for medium printing volumes



■ STACKER INCLUDED IN THE STANDARD DEVICE



■ WIDE-RANGING FUNCTIONS

Profitable functions like
- integrated form management
- n-times format splitting
- SPS-control
by MICROPLEX MPC high-end controller

■ 100% PRINT CONTROL

Status-out page-control gives notice of each correctly printed page via interface

■ MOST LOW-PRICED COLD FUSER AT THE MARKET WITH 17 INCH PRINT WIDTH

■ SAP- AND AS/400-COMPATIBLE

by PCL 5e + Jetcaps and LAN-IPDS

MICROPLEX
Printware AG
Panzerstraße 5
D-26316 Varel

Tel. +49.4451.9137.0
Fax +49.4451.81063
Email info@microplex.de

www.microplex.de

SOLID 85E

Specifications

The low operating costs, the low cost price as well as the max. paper width of 18 inch make the SOLID 85E the most economic printer of this class of performance. The cold fusing via Xenon flash lamps enables the manufacturing of thermic sensitive media. Even on thick material the fusing takes place without any problems.


Print Engine

Print technology	LED, OPC Xenon flash lamp with halogen preheat
Controller	MPC 3.x with Intel CPU (>2 GHz CISC Processor)
Print speed	3000 lpm (6 lpi) 12,7 m/min up to 85 pages/minute (A4 2-up)
Resolution	max. 600 dpi x 600 dpi
Recommended monthly print volume	up to 750.000 pages (A4 2-up) (based on a using period of 60 month)
Power supply	230V +/-10% /50 Hz max. 5.5 KVA (in operation) max. 0,6 KVA (in stand-by)
Dimensions(WxDxH in mm)	780 x 890 x 1320 780 x 935 x 1320
Weight (incl. Stacker)	275 kg
Environment	Relative Feuchte 30 - 80 % (in operation) Temperatur 15 - 35°C (in operation)
Interfaces	serial parallel network USB 2.0 IEEE 1284 Ethernet-Interface 10/100 Mbit, bi-direktional (TCP/IP)
Memory	serial RAM Flash 512 MB 64 MB

MPC 3.x High-End Print-Controller

Emulations	MICROPLEX IDOL HP PCL 5e Epson FX-80	IBM Proprinter Diablo 630 µ-Postscript TIFF
Optional Emulationd	Printronix IGP PGL, ZPLII Datamax, EPL	Magnum Code V Kycocera Prescribe Express IPDS (more Emulations on request)
Barcodes	EAN 8, 13, 128, add on 2/5 3-stroke Datalogic 2/5 3-stroke Matrix Codabar, PDF 417 Royalbar, Planet	Jetcaps (HP/SAP) Code 39 128 MSI UPC A, E Postnet, KIX USPS One Code
Optional Barcodes	USD5 Aztec-Code	UPS-Maxicode Datamatrix (more Barcodes on request)
Functions	Intelligent barcode generation on-the-fly in the printer	
	Format splitting in several subformats by command	
	Integrated form management up to 12 MB flash for forms and fonts inside the printer	
Optional Functions	Status-out gives notice of each correctly printed page via interface	
	SPS-control integration of the printer into production lines is possible, controlled by SPS-interface.	

Paper Path



Feeder/Stacker

Input	push tractor
Output	stacker capacity: 3.000 pages (at 64 g/m ²)

Media

Size	form length form length with stacker	7" - 24" 8" - 14"
	form width printable area	6" - 18" 17"
Weight	60 - 204 g/m ²	